



Toll Free: 87 PERMATEX
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex® Ultra Slick™ Engine Assembly Lube

AAM Revised 10/02

PRODUCT DESCRIPTION

S.I.N.: 834-300

Permatex® Ultra Slick™ Engine Assembly Lube is a red, tacky lubricant, which is a proven pre-lubricant for all gasoline and diesel engines. Its tacky lubricating film forms a protective coating during assembly and critical start-up and wear-in periods. Permatex® Ultra Slick™ Engine Assembly Lube base oils are highly refined and fortified with a unique blend of extreme pressure (EP) additives. These additives enhance and sustain the anti-scuffing, galling and wear-in properties of the product.

PRODUCT BENEFITS


- Excellent adhesion to metal surfaces; will not drain off during assembly
- EP agents that work in unison for superior wear-in protection needed prior and during initial engine start up
- Treated with special rust and high temperature oxidation inhibitors
- Exceeds all OEM specifications as an engine and bearing assembly lubricant

TYPICAL APPLICATIONS

- Engine bearings
- Camshafts and lifters
- Rocker arms
- Valves and guides
- Rocker shift assemblies
- Timing components

DIRECTIONS FOR USE

1. Apply a liberal coating to engine bearings, camshaft and lifters, and on timing components as the engine is being assembled.



PROPERTIES OF UNCURED MATERIAL

| | Typical Value |
|-------------------------|-----------------------|
| Chemical Type | Petroleum distillates |
| Appearance | Red liquid |
| Odor | Mild petroleum |
| Viscosity | Tacky gel |
| Specific Gravity | 0.91 |
| Flash Point, C.O.C., _F | 560 |

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a lubricant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

| Part Number | Container Size |
|-------------|----------------|
| 81950 | 4 oz. bottle |

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8_ to 28_C (46_ to 82_F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.