

Wheel Stop™

Fits 26" to 30" diameter tires with tire spacing of 1-½" to 3-½"

- Helps prevent trailer movement
- Easy to use, easy to store
- Fits trailers with shorter distance between tandem wheels
- Stabilizes your trailer

Place Wheel Stop™ between your tandem tires to help prevent both forward and backward movement while parked or re hitching. Wheel Stop™ installs easily between tires, stabilizing your trailer with one piece of equipment.



Directions:

1. Turn knob counterclockwise to open.
2. Place Wheel Stop™ between tires as shown
3. While holding lower wedge, turn knob clockwise, bringing lower wedge in contact with tires.
4. Continue to turn knob clockwise until Wheel Stop™ is securely seated between tires.

IMPORTANT: After leveling trailer, verify Wheel Stop™ is secure. If not, reseal and tighten.

CAUTION: This product is intended to help stabilize a recreational vehicle and is not intended for use on heavy commercial type trucks or trailers. Always use brake and wheel chocks to safely secure vehicle. Never place yourself under or behind an unstable vehicle. Prolonged exposure to sunlight can cause Wheel Stop™ wedges to weaken. Store out of sunlight in a dry, dark place. Read, study, understand and follow all instructions before using this product. Failure to heed these warnings may result in personal injury and or property damage.

Our return policy is limited to the replacement of original purchase. No other liability, responsibility or warranty is expressed or implied, including any regarding merchantability or suitability for a particular purpose.

Camco Manufacturing, Inc.
121 Landmark Dr. / Greensboro, NC 27409
1-800-334-2004 / www.camco.net

z885208