



PRODUCT FACT SHEET

TLR-2®/ TLR-2®s RAIL MOUNTED TACTICAL LIGHT WITH LASER SIGHT OR STROBING TACTICAL LIGHT WITH LASER SIGHT

MARKET

APPLICATIONS: Law Enforcement, Security, Military, Home Defense

DESCRIPTION:

Lightweight, compact, lithium battery powered Gun-Mounted Tactical Light with integrated aiming laser featuring the latest in shock-proof power LED technology and providing at least 2.5 hours of continuous run time when in dual mode with the high power visible laser. Rail clamp designed to rapidly attach/detach from side of weapon. Both models offer a tethered battery door and latch mechanism that prevents battery door loss while providing easy battery replacement. Strobe activated on two or more momentary paddle hits for guaranteed entry into strobe mode (TLR-2®s only).

CASE MATERIAL:

6000 Series machined aircraft aluminum with black anodized finish on main body. High impact, chemically resistant engineering polymer laser housing.

DIMENSIONS:

Length: 3.26 in. (8.28 cm) Width: 1.47 in. (3.73 cm) Height: 1.83 in. (4.64 cm)

WEIGHT:

4.72 oz (133.8 grams) with batteries (included in purchase).

LENS:

High temperature, shock mounted, impact resistant Boro Float glass.

LIGHT SOURCE:

C4®LED technology, impervious to shock with a 50,000 hour lifetime. 650-660nm red laser.

LIGHT OUTPUT:

8,000 candela peak beam intensity and 160 lumens measured system output. Deep-dish parabolic reflector produces a concentrated beam with optimum peripheral illumination. Laser provides long-range targeting.

ON/OFF:

Ambidextrous momentary/steady On-Off switch.
Three position Mode Selector switch (Laser only, LED Illumination only, both)
Double tap of momentary paddle within 0.4 seconds activates strobe. (TLR-2®s only)

RUN TIME:

2.5 hours regulated run time when using Laser/LED simultaneously.
Solid-state current regulation for consistent illumination level.

BATTERY:

Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.

FEATURES:

C4®LED technology
Ambidextrous momentary/steady On-Off switch.
One handed snap-on and tighten interface keeps hands away from muzzle when attaching/detaching. Securely fits a broad range of weapons.
Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails.
Includes keys for Glock-style, Picatinny, Beretta 90two, S&W 99 and S&W TSW.
Extensively live-fire tested impact resistant construction.
Windage and Elevation adjustment screws mounted in brass bushings for long life and dependable zero retention.
Highly accurate sight repeatability when remounting.
Operating temperature: -40°F to +120°F.
IPX4 rated design for water resistant operation.
User programmable strobe enable/disable. (TLR-2®s only)

APPROVALS:

Meets applicable European Community Directives. 

WARRANTY:

Streamlight's Limited Lifetime Warranty.

**OPTIONAL
ACCESSORIES:**

Mounting Adapters, Remote Switches, Filters