

2012 VIERA®

C5 Series LED LCD



Available Model:
TC-L32C5

Screen image simulated.

720P LCD

Enjoy 720p HD resolution for vivid, lifelike images.

USB PLAYER

View your saved photos and music from the convenient USB port.

-
- 24p Playback
 - Eco Mode
 - Game Mode
 - 2 HDMI / 1 USB / 1 PC



2012 VIERA®

C5 Series LED LCD

DISPLAY		TC-L32C5
Screen Size Diagonal (inches)		31.5
Aspect Ratio		16:9
Number of Pixels		1,049,088 (1,366 x 768)
Panel		LCD
HDTV Display Capability (1080p, 1080i, 720p)		Y
Aspect Control		480i/p: FULL, JUST, 4:3, ZOOM 1080i/p: FULL, H-FLL, JUST, 4:3, ZOOM
PICTURE		
Viewing Angle		176 degrees
Filter		—
Panel Drive		60 Backlight Scanning
24p Playback (3:2) / 24p Smooth Film		Y / —
24p Cinematic Playback		—
ISFccc		—
Intelligent Scene Controller		Y
Pro Setting		—
Smart VIERA Engine Pro (Dual core processor)		—
	Pure Image Creation	—
	Vivid Color Creation	—
	Facial Retouch	—
	Web Contents Smoother	—
	1080p Pure Direct	—
FULL HD 3D		
3D Panel		—
3D 24p Cinema Smoother		—
2D-3D Conversion		—
Dedicated 3D Eyewear		—
AUDIO		
3D Real Sound		—
Number of Speakers		2
Audio Output		10 W
Surround Sound		AV Surround
JACKS		
Integrated ATSC Tuner		Y
HDMI Input		2
	Support Feature	—
SD Card		—
USB 2.0		1
Analog Audio Input (for HDMI / DVI)		Y (Mini jack)
Composite Video Input shared with Component		RCA x 1
Audio Input (for Composite Video)		RCA x 1
PC Input		D-sub 15-pin x 1
Component Video Input (Y, Pb, Pr) shared with Composite		RCA x 1
Audio Input (for Component Video)		RCA x 1
Ethernet		—
Digital Audio Output		1
FEATURES		
VIERA Connect™ (IPTV)		—
Online Movies		—
Web Browser		—
Skype™ While Watching TV		—
Multitasking		—
Social Networking TV (Facebook / Twitter)		—
VIERA Remote App Support		—
VIERA Touch Pad Controller		—
Wireless LAN Adaptor		—
DLNA		—
Media Player		Y (USB)
	Support Format	JPEG / MP3
VIERA Link		—
VIERA Tools		—
Eco Mode		Y
Game Mode		Y
Trilingual Menu (English / Spanish / French)		Y
Built-In Closed Caption Decoder		Y
Off-Timers		Y
E-Help		—
GENERAL		
Power Supply		AC 110-127 V, 60 Hz
On Mode Average Power Consumption		—
Receiving System		ATSC / QAM / NTSC
Dimensions with Stand	Height (inches (mm))	—
	Width (inches (mm))	—
	Depth (inches (mm))	—
Dimensions without Stand	Height (inches (mm))	—
	Width (inches (mm))	—
	Depth (inches (mm))	—
Weight with Stand (lbs (kg))		—
Weight without Stand (lbs (kg))		—
Carton Dimensions	Height (inches (mm))	—
	Width (inches (mm))	—
	Depth (inches (mm))	—
Gross Weight (lbs (kg))		—
Operating Temperature		32°F-95°F (0°C-35°C)
Safety Standard		US: UL60065/FCC Part15, CANADA: CSA C22.2/IC 8ETS-7
Swivel Angle		—
VESA Compatible		Y
Optional Wall-mounting Bracket Model Numbers		TY-WK3L2RW
Glass & Metal Design		—

*with Special Adapter Cable (dedicated)

03/12 Specifications subject to change without notice.

Panasonic
ideas for life

VIERA

Official Worldwide
Olympic Partner

