

## HD66 – Home Theater Projector

### Home Theater Projector Delivers the Future

Breathtaking and bold, the Optoma HD66 home theater projector provides stunningly beautiful widescreen viewing. With 2500 ANSI lumens and 4000:1 contrast, the HD66 delivers subtle details and striking clarity for pure viewing delight.

\* 3D content can be viewed with active LCD shutter glasses when the projector is connected to a computer with a compatible 3D graphics card. Please visit [www.optoma.com](http://www.optoma.com) for more information.



### Features

- DLP® by Texas Instruments with BrilliantColor™ Technology
- Bright images and high contrast ratio – 2500 ANSI lumens and 4000:1 contrast ratio (full on/full off)
- Rapid power-on and shutdown – saving you time and money
- Longer lamp life – up to 4000 hrs

### Specifications

#### Display Type

Single 0.65" DMD DLP Technology by Texas Instruments

#### Resolution

HD (1280x720)

#### Maximum Resolution

UXGA (1600 x 1200)

#### Brightness (Typical)

2500 ANSI Lumens

#### Contrast Ratio

4000:1 (Full On/Full Off)

#### Lamp Life and Type\*

4000/3000 Hours (STD/Bright)  
185W P-VIP

#### Throw Ratio

1.55 to 1.7 (Distance/Width)

#### Projection Distance

3.28' to 32.8' (1.0 to 10m)

#### Image Size (Diagonal)

27.2" to 301" (0.69 to 7.65m)

#### Offset

112%

#### Displayable Colors

1.07 Billion

#### Uniformity

85%

#### Audio

2-Watt Speaker

#### Remote Control

IR Remote

#### Computer Compatibility

UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible

#### Video Compatibility

NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)

#### 3D Compatibility

120Hz Frame Sequential 3D for Resolutions Up to 720p, 60Hz Field Sequential 3D for Resolutions Up to 480i

#### Projection Lens

F=2.5-2.67, f=21.8-24mm, 1.1x Manual Zoom and Focus

#### User Controls

Complete On-Screen Menu Adjustments in 23 Languages

#### I/O Connectors

HDMI, VGA-In, S-Video, Composite Video, Stereo Audio-In and RS-232

#### Security

Kensington® Lock Port, Security Bar and Keypad Lock

#### Projection Method

Front, Rear, Ceiling Mount, Table Top

#### Weight

5.1 lbs (2.31kg)

#### Dimensions (W x H x D)

11.28" x 3.98" x 7.6"  
(287 x 101 x 193 mm)

#### Noise Level (STD/BRIGHT)

28dB/30dB

#### Keystone Correction

±40° Vertical



#### Horizontal Scan Rate

15.3 - 91.1 KHz

#### Vertical Refresh Rate

24 - 120 Hz

#### Operating Temperature

41 to 104°F (5 to 40°C), 85% Max Humidity

#### Power Supply

AC Input 100-240V, 50-60Hz, Auto-Switching

#### Power Consumption

255 Watts (Bright), 207 Watts (STD), <1 Watt (Standby)

#### Standard Accessories

AC Power Cord, Composite Cable, VGA to Component Cable, Remote Control, Batteries for Remote, Lens Cap, Multilingual CD-ROM User's Manual, Quick Start Card and Warranty Card

#### Optional Accessories

HDMI cable, Ceiling Mount, S-Video Cable, Composite Video Cable, RS-232 Cable and Panoview™ Series Screens

#### Warranty

1 Year Limited Parts and Labor, 90 Days on Lamp

#### UPC

796435 81 114 3

#### Accessory Part Numbers

Lamp: BL-FU185A  
Remote: BR-3048N  
Mount: BM-5001U  
Case: BK-4006

\* Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.