

2012 VIERA®

E5 Series LED LCD

SMARTVIERA



Screen image simulated.

Available Models:

TC-L47E5
TC-L42E5
TC-L37E5
TC-L32E5

IPS FULL HD LED PANEL

Enjoy brighter, clearer HD images from anywhere in the room.

ONLINE MOVIES¹, WI-FI READY

Access your favorite online entertainment straight from your TV.

MEDIA PLAYER (SD AND USB)

Enjoy your photos and video clips on the big screen.

CLEAR PANEL

Improves picture performance with high contrast and bright, clear images.

- 178° Viewing Angle
- 180 Backlight Scanning
- DLNA
- VIERA Remote App Support
- VIERA Link
- 4 HDMI / 2 USB / 1 SD Card Slot / 1 PC

STEP-UP FEATURES



¹Broadband Internet service required.

Panasonic
ideas for life

VIERA

Official Worldwide
Olympic Partner



2012 VIERA® E5 Series LED LCD

	TC-L47E5	TC-L42E5	TC-L37E5	TC-L32E5
DISPLAY				
Screen Size Diagonal (inches)	47.0	42.0	36.5	31.5
Aspect Ratio	16:9	16:9	16:9	16:9
Number of Pixels	2,073,600 (1,920 x 1,080)			
Panel	IPS LED LCD	IPS LED LCD	IPS LED LCD	IPS LED LCD
HDTV Display Capability (1080p, 1080i, 720p)	Y	Y	Y	Y
Aspect Control	480i/p: FULL, JUST, 4:3, ZOOM 1080i/p: FULL, H-FILL, JUST, 4:3, ZOOM	480i/p: FULL, JUST, 4:3, ZOOM 1080i/p: FULL, H-FILL, JUST, 4:3, ZOOM	480i/p: FULL, JUST, 4:3, ZOOM 1080i/p: FULL, H-FILL, JUST, 4:3, ZOOM	480i/p: FULL, JUST, 4:3, ZOOM 1080i/p: FULL, H-FILL, JUST, 4:3, ZOOM
PICTURE				
Viewing Angle	178 degrees	178 degrees	178 degrees	178 degrees
Filter	Clear Panel	Clear Panel	Clear Panel	Clear Panel
Panel Drive	180 Backlight Scanning	180 Backlight Scanning	180 Backlight Scanning	180 Backlight Scanning
24p Playback (3:2) / 24p Smooth Film	Y / —	Y / —	Y / —	Y / —
24p Cinematic Playback	—	—	—	—
ISFccc	—	—	—	—
Intelligent Scene Controller	Y	Y	Y	Y
Pro Setting	—	—	—	—
Smart VIERA Engine Pro (Dual core processor)	—	—	—	—
Pure Image Creation	—	—	—	—
Vivid Color Creation	Y	Y	Y	Y
Facial Retouch	—	—	—	—
Web Contents Smoother	—	—	—	—
1080p Pure Direct	—	—	—	—
FULL HD 3D				
3D Panel	—	—	—	—
3D 24p Cinema Smoother	—	—	—	—
2D-3D Conversion	—	—	—	—
Dedicated 3D Eyewear	—	—	—	—
AUDIO				
3D Real Sound	Y	Y	Y	Y
Number of Speakers	2	2	2	2
Audio Output	20 W	20 W	20 W	20 W
Surround Sound	AV Surround	AV Surround	AV Surround	AV Surround
JACKS				
Integrated ATSC Tuner	Y	Y	Y	Y
HDMI Input	4 (4 side)	4 (4 side)	4 (4 side)	4 (4 side)
Support Feature	Audio Return Channel (Input 2)			
SD Card	Y (SDXC)	Y (SDXC)	Y (SDXC)	Y (SDXC)
USB 2.0	2	2	2	2
Analog Audio Input (for HDMI / DVI)	Y	Y	Y	Y
Composite Video Input shared with Component	RCA x 1 (lower)*			
Audio Input (for Composite Video)	RCA x 1 (lower)*			
PC Input	D-sub 15-pin x 1 (lower)			
Component Video Input (Y, Pb, Pr) shared with Composite	RCA x 1 (lower)*			
Audio Input (for Component Video)	RCA x 1 (lower)*			
Ethernet	1 (lower)	1 (lower)	1 (lower)	1 (lower)
Digital Audio Output	1 (lower)	1 (lower)	1 (lower)	1 (lower)
FEATURES				
VIERA Connect™ (IPTV)	—	—	—	—
Online Movies	Y	Y	Y	Y
Web Browser	—	—	—	—
Skype™ While Watching TV	—	—	—	—
Multitasking	—	—	—	—
Social Networking TV (Facebook / Twitter)	—	—	—	—
VIERA Remote App Support	Y	Y	Y	Y
VIERA Touch Pad Controller	—	—	—	—
Wireless LAN Adaptor	WiFi Ready	WiFi Ready	WiFi Ready	WiFi Ready
DLNA	Y	Y	Y	Y
Media Player	Y (SD Card / USB)			
Support Format	AVCHD Progressive / SD-VIDEO / MotionJPEG (Lumix) / MKV / MP4 / MOV / M4v / FLV / 3GPP / VRO / VOB / TS / PS, MP3 / AAC / FLAC, JPEG	AVCHD Progressive / SD-VIDEO / MotionJPEG (Lumix) / MKV / MP4 / MOV / M4v / FLV / 3GPP / VRO / VOB / TS / PS, MP3 / AAC / FLAC, JPEG	AVCHD Progressive / SD-VIDEO / MotionJPEG (Lumix) / MKV / MP4 / MOV / M4v / FLV / 3GPP / VRO / VOB / TS / PS, MP3 / AAC / FLAC, JPEG	AVCHD Progressive / SD-VIDEO / MotionJPEG (Lumix) / MKV / MP4 / MOV / M4v / FLV / 3GPP / VRO / VOB / TS / PS, MP3 / AAC / FLAC, JPEG
VIERA Link	Y	Y	Y	Y
VIERA Tools	Y	Y	Y	Y
Eco Mode	Y	Y	Y	Y
Game Mode	Y	Y	Y	Y
Bilingual Menu (English / Spanish / French)	Y	Y	Y	Y
Built-In Closed Caption Decoder	Y	Y	Y	Y
Off-Timers	Y	Y	Y	Y
E-Help	—	—	—	—
GENERAL				
Power Supply	AC 110-127 V, 60 Hz			
On Mode Average Power Consumption	60.2 W (TBD)	46.0 W (TBD)	45.3 W (TBD)	33.8 W (TBD)
Receiving System	ATSC / QAM / NTSC			
Dimensions with Stand	Height (inches (mm))	28.1" (712 mm)	25.6" (650 mm)	22.9" (581 mm)
	Width (inches (mm))	43.6" (1,107 mm)	39.3" (997 mm)	34.4" (874 mm)
	Depth (inches (mm))	10.6" (268 mm)	9.8" (247 mm)	9.4" (238 mm)
Dimensions without Stand	Height (inches (mm))	26.3" (666 mm)	23.8" (604 mm)	21.1" (534 mm)
	Width (inches (mm))	43.6" (1,107 mm)	39.3" (997 mm)	34.4" (874 mm)
	Depth (inches (mm))	Max: 2.1" (52 mm); General: 1.6" (40 mm)	Max: 2.1" (52 mm); General: 1.6" (40 mm)	Max: 2.1" (52 mm); General: 1.6" (40 mm)
Weight with Stand (lbs (kg))	44.1 lbs. (20.0 kg)	37.5 lbs. (17.0 kg)	29.8 lbs. (13.5 kg)	24.3 lbs. (11.0 kg)
Weight without Stand (lbs (kg))	36.4 lbs. (16.5 kg)	30.9 lbs. (14.0 kg)	25.4 lbs. (11.5 kg)	19.9 lbs. (9.0 kg)
Carton Dimensions	Height (inches (mm))	30.9" (784 mm)	28.4" (721 mm)	25.1" (636 mm)
	Width (inches (mm))	52.5" (1,331 mm)	47.6" (1,208 mm)	45.8" (1,163 mm)
	Depth (inches (mm))	6.4" (162 mm)	5.5" (139 mm)	5.3" (134 mm)
Gross Weight (lbs (kg))	53.0 lbs. (24.0 kg)	46.3 lbs. (21.0 kg)	35.3 lbs. (16.0 kg)	28.7 lbs. (13.0 kg)
Operating Temperature	32°F-95°F (0°C-35°C)	32°F-95°F (0°C-35°C)	32°F-95°F (0°C-35°C)	32°F-95°F (0°C-35°C)
Safety Standard	US: UL60065/FCC Part15, CANADA: CSA C22.2/IC BETS-7			
Swivel Angle	—	—	—	—
VESA Compatible	Y	Y	Y	Y
Optional Wall-mounting Bracket Model Numbers	—	—	TY-WK3L2RW	TY-WK3L2RW
Glass & Metal Design	—	—	—	—

*with Special Adapter Cable (dedicated)

03/12 Specifications subject to change without notice.

Panasonic
ideas for life

VIERA

Official Worldwide
Olympic Partner

