

2012 VIERA®

SMARTVIERA

DT50 Series LED LCD



Available Models:
TC-L55DT50
TC-L47DT50

Screen image simulated.

FULL HD 3D

Immerse yourself in stunning realism that jumps off the screen.

IPS LED PANEL

Enjoy brighter and clearer images from almost anywhere in the room.

METAL AND GLASS COSMETIC DESIGN

A breathtaking design adds an instant sophistication to any décor.

VIERA CONNECT™¹ WI-FI BUILT-IN WITH WEB BROWSER

Stay connected wirelessly to your favorite Web content, sports, movies and so much more.

- Clear Panel Pro
- 1920 Backlight Scanning
- 178° Viewing Angle
- 2D-3D Conversion
- 24p Cinematic Playback
- Media Player (SD and USB)
- DLNA
- VIERA Remote App Support
- Skype™ Video Calling²
- Social Networking TV
- VIERA Link
- 4 HDMI / 3 USB / 1 SD Card Slot / 1 PC
- 3D Real Sound
- Swivel Base

STEP-UP FEATURES



¹Broadband Internet service required.

²Optional communication camera required.

Panasonic
ideas for life

VIERA

Official Worldwide
Olympic Partner



2012 VIERA®

DT50 Series LED LCD

	TC-L55DT50	TC-L47DT50	
DISPLAY			
Screen Size Diagonal (inches)	54.6	47.0	
Aspect Ratio	16:9	16:9	
Number of Pixels	2,073,600 (1,920 x 1,080)	2,073,600 (1,920 x 1,080)	
Panel	IPS LED LCD	IPS LED LCD	
HDTV Display Capability (1080p, 1080i, 720p)	Y	Y	
Aspect Control	480i/p: FULL, JUST, 4:3, ZOOM 1080i/p: FULL, H-FILL, JUST, 4:3, ZOOM	480i/p: FULL, JUST, 4:3, ZOOM 1080i/p: FULL, H-FILL, JUST, 4:3, ZOOM	
PICTURE			
Viewing Angle	178 degrees	178 degrees	
Filter	Clear Panel Pro	Clear Panel Pro	
Panel Drive	1920 Backlight Scanning	1920 Backlight Scanning	
24p Playback (3:2) / 24p Smooth Film	Y / Y	Y / Y	
24p Cinematic Playback	48 Hz	48 Hz	
ISFccc	—	—	
Intelligent Scene Controller	Y	Y	
Pro Setting	—	—	
Smart VIERA Engine Pro (Dual core processor)	—	—	
Pure Image Creation	—	—	
Vivid Color Creation	Y	Y	
Facial Retouch	—	—	
Web Contents Smoother	Y	Y	
1080p Pure Direct	—	—	
FULL HD 3D			
3D Panel	Y (Active)	Y (Active)	
3D 24p Cinema Smoother	Y	Y	
2D-3D Conversion	Y	Y	
Dedicated 3D Eyewear	—	—	
AUDIO			
3D Real Sound	Y	Y	
Number of Speakers	Front speaker (8 train speakers) x 2, Woofer (ø75 mm) x 1	Front speaker (8 train speakers) x 2, Woofer (ø75 mm) x 1	
Audio Output	18 W (4 + 4 + 10)	18 W (4 + 4 + 10)	
Surround Sound	AV Surround	AV Surround	
JACKS			
Integrated ATSC Tuner	Y	Y	
HDMI Input	4 (4 side)	4 (4 side)	
Support Feature	Audio Return Channel (Input 2)	Audio Return Channel (Input 2)	
SD Card	Y (SDXC)	Y (SDXC)	
USB 2.0	3	3	
Analog Audio Input (for HDMI / DVI)	Y	Y	
Composite Video Input shared with Component	RCA x 1 (lower)*	RCA x 1 (lower)*	
Audio Input (for Composite Video)	RCA x 1 (lower)*	RCA x 1 (lower)*	
PC Input	D-sub 15-pin x 1 (lower)	D-sub 15-pin x 1 (lower)	
Component Video Input (Y, Pb, Pr) shared with Composite	RCA x 1 (lower)*	RCA x 1 (lower)*	
Audio Input (for Component Video)	RCA x 1 (lower)*	RCA x 1 (lower)*	
Ethernet	1 (lower)	1 (lower)	
Digital Audio Output	1 (lower)	1 (lower)	
FEATURES			
VIERA Connect™ (IPTV)	Y	Y	
Online Movies	—	—	
Web Browser	Y	Y	
Skype™ While Watching TV	Y	Y	
Multitasking	—	—	
Social Networking TV (Facebook / Twitter)	Y	Y	
VIERA Remote App Support	Y	Y	
VIERA Touch Pad Controller	—	—	
Wireless LAN Adaptor	Y (built-in)	Y (built-in)	
DLNA	Y	Y	
Media Player	Y (SD Card / USB)	Y (SD Card / USB)	
Support Format	AVCHD 3D / Progressive, SD-VIDEO / MotionJPEG (Lumix) / MKV / MP4 / MOV / M4v / FLV / 3GPP / VRO / VOB / TS / PS, MP3 / AAC / FLAC, JPEG / MPO	AVCHD 3D / Progressive, SD-VIDEO / MotionJPEG (Lumix) / MKV / MP4 / MOV / M4v / FLV / 3GPP / VRO / VOB / TS / PS, MP3 / AAC / FLAC, JPEG / MPO	
VIERA Link	Y	Y	
VIERA Tools	Y	Y	
Eco Mode	Y	Y	
Game Mode	Y	Y	
Trilingual Menu (English / Spanish / French)	Y	Y	
Built-In Closed Caption Decoder	Y	Y	
Off-Timers	Y	Y	
E-Help	Y	Y	
GENERAL			
Power Supply	AC 110-127 V, 60 Hz	AC 110-127 V, 60 Hz	
On Mode Average Power Consumption	85 W (TBD UNTIL Feb 28)	74.3 W (TBD UNTIL Jan 31)	
Receiving System	ATSC / QAM / NTSC	ATSC / QAM / NTSC	
Dimensions with Stand	Height (inches (mm))	30.5" (773 mm)	26.7" (677 mm)
	Width (inches (mm))	48.7" (1,237 mm)	42.0" (1,067 mm)
	Depth (inches (mm))	11.5" (290 mm)	10.5" (265 mm)
Dimensions without Stand	Height (inches (mm))	28.6" (726 mm)	24.9" (631 mm)
	Width (inches (mm))	48.7" (1,237 mm)	42.0" (1,067 mm)
	Depth (inches (mm))	1.1" (27 mm)	1.1" (27 mm)
Weight with Stand (lbs (kg))	49.6 lbs. (22.5 kg)	37.5 lbs. (17.0 kg)	
Weight without Stand (lbs (kg))	37.5 lbs. (17.0 kg)	28.7 lbs. (13.0 kg)	
Carton Dimensions	Height (inches (mm))	29.7" (754 mm)	29.7" (754 mm)
	Width (inches (mm))	58.3" (1,480 mm)	58.3" (1,480 mm)
	Depth (inches (mm))	4.8" (120 mm)	4.8" (120 mm)
Gross Weight (lbs (kg))	64.0 lbs. (29.0 kg)	48.5 lbs. (22.0 kg)	
Operating Temperature	32°F-95°F (0°C-35°C)	32°F-95°F (0°C-35°C)	
Safety Standard	US: UL60065/FCC Part15, CANADA: CSA C22.2/IC BETS-7	US: UL60065/FCC Part15, CANADA: CSA C22.2/IC BETS-7	
Swivel Angle	±15°	±15°	
VESA Compatible	Y	Y	
Optional Wall-mounting Bracket Model Numbers	—	—	
Glass & Metal Design	Y (Narrow Metal Frame)	Y (Narrow Metal Frame)	

*with Special Adapter Cable (dedicated)

03/12 Specifications subject to change without notice.

Panasonic
ideas for life

VIERA

Official Worldwide
Olympic Partner

