2011 VIERA®
E30 Series LED/ LCD

Screen image simulated.

IPS ALPHA LED PANEL
Delivers a 178° wide viewing angle for bright, clear and vivid images from virtually anywhere in the room.

120 HZ MOTION PICTURE PRO 4
Sports and fast-action stay crisp and focused, with minimal motion blur.

EASY IPTV
Enjoy great Web entertainment with just a click of your remote.

VIERA IMAGE VIEWER (PHOTO & MOVIE)
View your digital photos and videos on your VIERA HDTV.

- 1080p Full HD Resolution
- Clear Panel
- Game Mode
- DLNA
- VIERA Link™

- 4 HDMI
- 2 USB
- PC Input
- 24p Smooth Film

IPS Alpha Panel
LED LCD TV
120Hz motion picture pro4
@EASY IPTV
VIERA IMAGE VIEWER
GAME MODE
dlna CERTIFIED

Panasonic® | VIErA

	TC-L42E30
VIDEO	
Screen Size Diagonal (in)	42.0
Aspect Ratio	16:9
Panel	IPS Alpha LED LCD 1080p (WSXGA)
Filter	Clear Panel
Number of Pixels	2,073,600 (1,920 x 1,080)
Moving Picture Resolution	900 lines
Viewing Angle	178 degrees
HDTV Display Capability (1080p, 1080i, 720p)	Y
EDTV Display Capability (480p)	Y
Aspect Control	480i/ p: FULL, JUST, 4:3, ZOOM 1080i/ p: FULL, H-FILL, JUST, 4:3, ZOOM
Progressive Scan	Y
Panel Drive	120 Hz
24p Smooth Film	Y
24p Playback	Y
x.v.Color	—
Intelligent Scene Controller	Y
Motion Focus Technology	Y
Super Resolution	Y
FULL HD 3D	
3D Panel	—
3D 24p Smooth Film	—
2D-3D Conversion	—
3D Image Viewer	—
3D Active Shutter Eyewear	—
AUDIO	
Speakers	Full-range x 2 (L, R)
Number of Speakers	2
Audio Output	20 W
Surround Sound	V-Audio Surround
JACKS	
Integrated ATSC Tuner	Y
VIERA Image Viewer	Y (AVCHD/ MPEG2/ JPEG/ MP3 playback)
HDMI	Input	4 (1 side)
	Support Feature	Audio Return Channel (Input 1)
USB	2
Analog Audio Input (for HDMI/DVI)	Y
Composite Video Input	RCA x 1
Audio Input (for Video)	RCA x 1
PC Input	D-sub 15-pin x 1
Component Video Input (Y, PB, PR)	RCA x 1
Audio Input (for Component Video)	RCA x 1
LAN Port	1
Digital Audio Output	1 (5.1 ch)
CONVENIENCE	
VIERA Link	Y
VIERA Connect (IPTV)	—
Easy IPTV	Y
Wireless LAN Adaptor	Wi-Fi Ready
Universal Dock for iPod	—
VIERA Tools	Y
DLNA	Y
Game Mode	Y
Trilingual Menu (English/Spanish/French)	Y
Built-In Closed Caption Decoder	Y
Sleep Off-Timers and Programable Timer (5 programs)	Y
GENERAL	
Power Supply	AC 110 – 127 V, 60 Hz
On Mode Average Power Consumption	54 W
Receiving System	ATSC/ QAM/ NTSC
Dimensions with stand	Height [in (mm)]	25.5" (646 mm)
	Width [in (mm)]	39.5" (1,002 mm)
	Depth [in (mm)]	11.4" (288 mm)
Dimensions without stand	Height [in (mm)]	24.1" (611 mm)
	Width [in (mm)]	39.5" (1,002 mm)
	Depth [in (mm)]	1.7" (41 mm)
Mass Weight with stand [lbs (kg)]	41.9 lbs. (19.0 kg)
Mass Weight without stand [lbs (kg)]	33.1 lbs. (15.0 kg)
Swivel Angle	—
Tilt Angle	—
VESA Compatible	Y
Carton Dimensions	Height [in (mm)]	28.9" (734 mm)
	Width [in (mm)]	46.8" (1,188 mm)
	Depth [in (mm)]	8.2" (207 mm)
Gross Weight [lbs (kg)]	48.5 lbs. (22.0 kg)
Optional Wall-mounting Bracket Model Numbers	TY-WK3L2RW

Panasonic | **VIErA**