

2011 VIERA® GT30 Series Plasma



Available Models:

TC-P50GT30

TC-P55GT30

TC-P60GT30

TC-P65GT30

FULL HD 3D

Revolutionary VIERA Full HD 3D Technology delivers award-winning realism that immerses you in the image.

FLUSH DESIGN

Trim and elegant to complement any décor.

INFINITE BLACK 2 PANEL

Delivers deep blacks and minimizes reflection for bright, vivid images.

VIERA CONNECT WI-FI READY

Enjoy a world of movies, sports and other online apps plus free Skype™ video calls on your VIERA HDTV.

- THX
- Fast Switching Phosphors
- 600 Hz Sub-field Drive
- 1080p Full HD Resolution
- Game Mode
- Motion Smoother
- Skype™ video calling*
- VIERA Image Viewer H.264 with 3D playback (Movie and Photo capable)
- DNLA
- VIERA Link™
- PC Input
- 4 HDMI
- 3 USB
- Mercury and Lead-Free Panel
- Long Panel Life (up to 100,000 Hours)



*Optional Skype camera required.

Panasonic VIERA

2011 VIERA®

GT30 Series Plasma

Subject to change

	TC-P65GT30	TC-P60GT30	TC-P55GT30	TC-P50GT30
VIDEO				
Screen Size Diagonal (in)	64.7	60.1	55.1	49.9
Aspect Ratio	16:9	16:9	16:9	16:9
Number of Pixels	2,073,600 (1,920 x 1,080)			
Moving Picture Resolution	1,080 lines	1,080 lines	1,080 lines	1,080 lines
Shades of Gradation	6,144 equivalent	6,144 equivalent	6,144 equivalent	6,144 equivalent
HDTV Display Capability (1080p, 1080i, 720p)	Y	Y	Y	Y
EDTV Display Capability (480p)	Y	Y	Y	Y
Aspect Control	4:3, ZOOM, FULL, JUST, H-FILL FOR TV/ AV MODES; 4:3, FULL FOR PC MODE	4:3, ZOOM, FULL, JUST, H-FILL FOR TV/ AV MODES; 4:3, FULL FOR PC MODE	4:3, ZOOM, FULL, JUST, H-FILL FOR TV/ AV MODES; 4:3, FULL FOR PC MODE	4:3, ZOOM, FULL, JUST, H-FILL FOR TV/ AV MODES; 4:3, FULL FOR PC MODE
Louver Filter	Y	Y	Y	Y
600 Hz Sub-field Drive	Y	Y	Y	Y
24p Cinematic Playback	—	—	—	—
24p Playback (2 : 3)	Y	Y	Y	Y
Deep Color	Y	Y	Y	Y
x.v.Color	Y	Y	Y	Y
THX Mode	Y	Y	Y	Y
ISFccc	—	—	—	—
Pro Setting	Y	Y	Y	Y
Super Resolution	Y	Y	Y	Y
3D Color Management	Y	Y	Y	Y
Sub Pixel Control	Y	Y	Y	Y
Motion Pattern Noise Reduction	Y	Y	Y	Y
FULL HD 3D				
3D Panel	Y	Y	Y	Y
3D 24p Cinema Smoother	Y	Y	Y	Y
2D-3D Conversion	Y	Y	Y	Y
3D Image Viewer	Y	Y	Y	Y
3D Active Shutter Eyewear	Not Included	Not Included	Not Included	Not Included
AUDIO				
Speakers	Full-range x 2 (L, R)	Dual Speaker, Woofer	Full-range x 2 (L, R)	Full-range x 2 (L, R)
Number of Speakers	2	2	2	2
Audio Output	20 W	20 W	20 W	20 W
CONEQ	—	—	—	—
Surround Sound	Y	Y	Y	Y
JACKS				
Integrated ATSC Tuner	Y	Y	Y	Y
VIERA Image Viewer	Y (AVCHD/ MPEG2/ JPEG/ MP3 playback)			
HDMI	Input	4 (4 side)	4 (4 side)	4 (4 side)
	Support Feature	Audio Return Channel (Input 1)/ 3D Input (All)	Audio Return Channel (Input 1)/ 3D Input (All)	Audio Return Channel (Input 1)/ 3D Input (All)
USB	3	3	3	3
Analog Audio Input (for HDMI/DVI)	Y	Y	Y	Y
Composite Video Input	RCA x 1 (lower)*			
Audio Input (for Video)	—	—	—	—
PC Input	D-sub 15-pin x 1 (rear)*			
Component Video Input (Y, PB, PR)	RCA x 1 (lower)*			
Audio Input (for Component Video)	RCA x 1 (lower)*			
LAN Port	1 (lower)	1	1	1
RS232C	—	—	—	—
Digital Audio Output (Optical)	1	1	1	1
CONVENIENCE				
VIERA Link	Y	Y	Y	Y
VIERA Connect (IPTV)	Y	Y	Y	Y
Easy IPTV	—	—	—	—
Wireless LAN Adaptor	Y	Y	Y	Y
VIERA Tools	Y	Y	Y	Y
DLNA	Y	Y	Y	Y
Game Mode	Y	Y	Y	Y
Pixel Orbiter (Anti-Image Retention)	Y	Y	Y	Y
Trilingual Menu (English/Spanish/French)	Y	Y	Y	Y
Built-In Closed Caption Decoder	Y	Y	Y	Y
Off-Timers	Y	Y	Y	Y
GENERAL				
Power Supply	AC 120 V, 60 Hz			
On Mode Average Power Consumption				
Receiving System	ATSC/ QAM/ NTSC	ATSC/ QAM/ NTSC	ATSC/ QAM/ NTSC	ATSC/ QAM/ NTSC
Dimensions with Stand	Height [in (mm)]	38.5" (978 mm)	35.7" (905 mm)	32.6" (827 mm)
	Width [in (mm)]	60.6" (1,538 mm)	55.8" (1,416 mm)	51.1" (1,297 mm)
	Depth [in (mm)]	15.8" (400 mm)	15.3" (387 mm)	15.3" (387 mm)
Dimensions without stand	Height [in (mm)]	37.0" (940 mm)	34.2" (868 mm)	31.1" (790 mm)
	Width [in (mm)]	60.6" (1,538 mm)	55.8" (1,416 mm)	51.1" (1,297 mm)
	Depth [in (mm)]	Speaker depth: 2.4" (59 mm); Panel depth: 1.5" (38 mm)	Speaker depth: 2.4" (59 mm); Panel depth: 1.5" (38 mm)	Speaker depth: 2.4" (59 mm); Panel depth: 1.5" (37 mm)
Weight with stand [lbs (kg)]			82.7 lbs. (37.5 kg)	65.1 lbs. (29.5 kg)
Weight without stand [lbs (kg)]			69.5 lbs. (31.5 kg)	56.3 lbs. (25.5 kg)
Operating Temperature	32°F – 104°F (0°C – 40°C)			
Safety Standard	UL6500/ C-UL	UL6500/ C-UL	UL6500/ C-UL	UL6500/ C-UL
Carton Dimensions	Height [in (mm)]			
	Width [in (mm)]			
	Depth [in (mm)]			
Gross Weight [lbs (kg)]				
Swivel Angle	—	—	—	±10°
One-Sheet-of-Glass Design	—	—	—	—
Optional Wall-mounting Bracket Model Numbers	TY-WK6P1RW	TY-WK5P1RW	TY-WK5P1RW	TY-WK4P1RW

*with Special Adapter Cable (dedicated)